

# MALLEABLE IRON COUPLINGS AND CONNECTORS



- Set Screw Couplings and Connectors
- Compression Couplings and Connectors
- Split Rigid Couplings
- Three-Piece Self-Aligning, Raintight Couplings
- Zinc Electroplated
- Exceptional strength and deformation properties


Malleable Iron product with exceptional elongation and deformation properties, corrosion resistance, and shock absorption. Zinc electroplated for enhanced corrosion resistance and extended life in areas that may be exposed to salt water and a variety of chemicals. Used in applications requiring exceptional strength such as warehouses, outdoor buildings, bridges and airports. Also used in power distribution applications.



# MALLEABLE IRON COUPLINGS AND CONNECTORS

## Set Screw Connectors

Set screw type fitting used to join unthreaded rigid or IMC conduit to box or enclosure. Concrete-tight.



1/2" thru 2"      5" & 6"

UL File No. E24001: 3500 thru 3509

\*Note: UL listing not applicable to 5" & 6" Malleable Iron.

### Malleable Iron / Insulated Throat - 105°C


Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
3510-I	5"	1	5
3511-I	6"	1	5

### Malleable Iron

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
3500	1/2"	50	200
3501	3/4"	25	250
3502	1"	25	100
3503	1 1/4"	20	120
3504	1 1/2"	10	60
3505	2"	5	30
3510	5"	1	5
3511	6"	1	5

## Set Screw Couplings

Set screw type fitting used to join two unthreaded lengths of rigid conduit. Concrete-tight. 1/2" thru 6" furnished with four set screws.



1/2" thru 2"      5" & 6"

UL File No. E24001\*: 3600 thru 3609

\*Note: UL listing not applicable to 5" & 6" Malleable Iron.

### Malleable Iron

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.	Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
3600	1/2"	30	120	3604	1 1/2"	10	60
3601	3/4"	25	100	3605	2"	5	30
3602	1"	25	100	3610	5"	1	5
3603	1 1/4"	15	90	3611	6"	1	5

## Compression Connectors

Compression type connector used to join unthreaded steel rigid conduit to box or enclosure.



UL File No. E9391

### Malleable Iron

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.	Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
3000	1/2"	25	100	3005	2"	1	5
3001	3/4"	25	100	3006	2 1/2"	2	10
3002	1"	5	25	3007	3"	2	10
3003	1 1/4"	5	25	3008	3 1/2"	---	6
3004	1 1/2"	2	10	3009	4"	---	6

## MIGHTY-ALIGN™, Raintight, Three-Piece Conduit Couplings

Used to join two lengths of threaded rigid and IMC conduit. Patented.



UL File No. E9391

### Malleable Iron

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.	Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
1121-RT	1/2"	25	100	1126-RT	2"	---	10
1122-RT	3/4"	10	100	1127-RT	2 1/2"	---	5
1123-RT	1"	5	50	1128-RT	3"	---	5
1124-RT	1 1/4"	-	25	1129-RT	3 1/2"	---	4
1125-RT	1 1/2"	-	20	1130-RT	4"	---	5

## Split Rigid Couplings

Split couplings used to join two lengths of threaded rigid and IMC conduit.



UL File No. E9391

### Zinc Plated Malleable Iron

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.	Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
SRC-050	1/2"	25	100	SRC-250	2 1/2"	---	5
SRC-075	3/4"	10	100	SRC-300	3"	---	5
SRC-100	1"	5	50	SRC-350	3 1/2"	---	4
SRC-125	1 1/4"	---	25	SRC-400	4"	---	5
SRC-150	1 1/2"	---	20	SRC-500	5"	---	2
SRC-200	2"	---	10	SRC-600	6"	---	1

## Compression Couplings

Compression type coupling used to join two lengths of unthreaded steel rigid conduit.



UL File No. E9391

### Malleable Iron

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.	Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
3100	1/2"	25	100	3105	2"	1	5
3101	3/4"	25	100	3106	2 1/2"	2	10
3102	1"	5	25	3107	3"	2	10
3103	1 1/4"	5	25	3108	3 1/2"	---	6
3104	1 1/2"	2	10	3109	4"	---	6



Printed in the U.S.A.

© 2010 Bridgeport Fittings, Inc. All rights reserved.

BP-152 9/10